

## XM1255

Offering three solutions in one easy-to-use package, the XM1255 makes applying adhesive to mockups, storyboards, or comps up to 11.75" wide fast and easy.

Instantly applies laminate, adhesive or both without heat or electricity. Simply feed the item in, turn the handle, and trim. No smell, no mess, no waiting.

- Aggressive adhesive, coupled with high pressure rollers, improves both transfer and bonding quality
- Patented drop-in cartridges allow quick and easy application changes
- Even, edge-to-edge adhesive application
- Environmentally safe



As easy as 1, 2, 3



1. Insert Item



2. Turn Handle



3. Trim

# XM1255

## Product Specifications

Footprint	10.5" x 13" x 15" (26.7cm x 33cm x 38.1cm)
Weight/Packed Weight	14.75lbs (6.6kg) / 18.25lbs (8.2kg)
Document Thickness (max.)	0.125" (3.2mm)
Finished Document Width (max.)	11.75" (29.8cm)
Power Requirements	None
Cutter	Removable, replaceable cutter



## Product Supply Description

- **Permanent High-Tack Adhesive:** Extremely aggressive adhesive instantly creates a permanent bond on most surfaces. Sets instantly and will not peel. Acid-Free.
- **Permanent Standard Adhesive:** Moderately aggressive adhesive creates a permanent bond on most surfaces. Can be touched to surface, peeled back quickly, and replaced. Acid-Free.
- **Repositionable Adhesive:** Allows items to be repositioned over and over. Easy removal from glass, walls, paper, and most other surfaces. Acid-Free.
- **Standard Use Laminate:** High gloss film suitable for use on a variety of substrates. Superior adhesion. Compatible with most media. Acid-Free.
- **Combination—Laminate/Adhesive:** One of the laminate products described on the top surface and one of the Acid-Free adhesives described on the bottom surface. Acid-Free.

The XM1255 is your complete professional document finishing system. Instantly applies laminate, adhesive or both. Perfect for presentations, comps, packaging mock-ups, signs, displays, and short-run labels.

Part Number	Product Description	Material Length	Material Width	Laminate & Adhesive Combination Thickness (per side)	Mounting Adhesive Thickness	Adhesive pH	Mounting Adhesive Strength (1:10; 10-high)	PAT Approved
<b>Adhesive Application Cartridges</b>								
● AT1251-100	Permanent High-Tack	100' (30.5m)	12" (30.5cm)	N/A	0.6mil (15.2mic)	Acid-Free	10	Yes
● AT1255-100	Permanent Standard	100' (30.5m)	12" (30.5cm)	N/A	0.6mil (15.2mic)	Acid-Free	8	Yes
● AT1256-100	Repositionable	100' (30.5m)	12" (30.5cm)	N/A	1.1mil (27.9mic)	Acid-Free	3	Yes
<b>Laminate Cartridges</b>								
● DL1251-150	2-Sided Standard Use Laminate	150' (95.7m)	12" (30.5cm)	2.7mil (67.5mic)	N/A	Acid-Free	N/A	Yes
<b>Combination One Side Lamination / One Side Adhesive Application</b>								
● LAT1251-100	1 Side Standard Use Laminate 1 Side High-Tack Adhesive	100' (30.5m)	12" (30.5cm)	2.7mil (67.5mic)	0.6mil (15.2mic)	Acid-Free	10	Yes
● LAT1256-100	1 Side Standard Use Laminate 1 Side Repositionable Adhesive	100' (30.5m)	12" (30.5cm)	2.7mil (67.5mic)	1.1mil (27.9mic)	Acid-Free	3	Yes
<b>Cutter</b>								
2342.01	Replaceable Cutter Bar and Blade Assembly							
2343.01	Replacement Tray							

## XM2500

Offering three solutions in one easy-to-use package, the XM2500 makes professional document, signage and poster finishing up to 25" wide fast and easy.

Instantly applies laminate, adhesive or both without heat or electricity. Simply feed the item in, turn the handle, and trim. No smell, no mess, no waiting.

- Aggressive adhesive, coupled with high pressure rollers, improves both transfer and bonding quality
- Patented supplies allow quick and easy application changes
- Even, edge-to-edge adhesive application
- Environmentally safe



### As easy as 1, 2, 3



1. Insert Item



2. Turn Handle



3. Trim

**HYATT'S**  
All Things Creative

[www.hyatts.com](http://www.hyatts.com)  
910 Main Street  
Buffalo, NY 14202

[art@hyatts.com](mailto:art@hyatts.com)  
PH: 1-800-234-9288 ext. 302  
FX: 1-716-884-3943

## XM2500

### Product Specifications

Footprint	18.5" x 28.125" x 15" (47cm x 71.4cm x 38.1cm)
Weight/Packed Weight	57lbs (25.9kg) / 72lbs (32.7kg)
Document Thickness (max.)	0.10" (2.5mm) up to 3/16" foam core
Finished Document Width (max.)	25" (63.5cm)
Power Requirements	None
Cutter	Removable, replaceable cutter



### Product Supply Description

- Permanent High-Tack Adhesive:** Extremely aggressive adhesive instantly creates a permanent bond on most surfaces. Sets instantly and will not peel. Acid-Free.
- Permanent Standard Adhesive:** Moderately aggressive adhesive creates a permanent bond on most surfaces. Can be touched to surface, peeled back quickly, and replaced. Acid-Free.
- Repositionable Adhesive:** Allows items to be repositioned over and over. Easy removal from glass, walls, paper, and most other surfaces. Acid-Free.
- Standard Use Laminate:** High-gloss film suitable for use on a variety of substrates. Superior adhesion. Compatible with most media. Acid-Free.
- Thermal Print Sensitive Laminate:** High-gloss film suitable for use on thermal print sensitive items. Acid-Free.
- Combination—Laminate/Adhesive:** One of the laminate products described on the top surface and one of the acid-free adhesives described on the bottom surface. Acid-Free.

The XM2500 is your complete professional document finishing system. Instantly applies laminate, adhesive or both without heat or electricity. Perfect for posters, displays, mock ups, banners and signs, advertisements, POP displays, and presentation-board.

Part Number	Product Description	Material Length	Material Width	Laminate & Adhesive Combination Thickness (per side)	Mounting Adhesive Thickness	Adhesive pH	Mounting Adhesive Strength (1:10; 10-high)	PAT Approved
<b>Adhesive Application Roll Set</b>								
AT400-300	Permanent High-Tack	300' (91.4m)	24.9" (63.4cm)	N/A	0.6mil (15.2mic)	Acid-Free	10	Yes
AT405-300	Permanent Standard	300' (91.4m)	24.9" (63.4cm)	N/A	0.6mil (15.2mic)	Acid-Free	8	Yes
AT406-170	Repositionable	170' (51.8m)	24.9" (63.4cm)	N/A	1.1mil (27.9mic)	Acid-Free	3	Yes
<b>Lamination Cartridges</b>								
DL403-300	2-Sided Standard Use Laminate	300' (91.4m)	25.3" (64.3cm)	2.7mil (67.5mic)	N/A	Acid-Free	N/A	Yes
DL404-300	2-Sided Thermal Print Sensitive Laminate General Use	300' (91.4m)	24.9" (63.4cm)	2.7mil (67.5mic)	N/A	Acid-Free	N/A	Yes
DL409-300	2-Sided Standard Use Thin Laminate	300' (91.4m)	24.9" (63.4cm)	1.7mil (43.8mic)	N/A	Acid-F	N/A	Yes
<b>Combination One Side Laminate / One Side Adhesive Application</b>								
LAT405-300	1 Side Standard Use Laminate 1 Side High-Tack Adhesive	300' (91.4m)	25.3" (64.3cm)	2.7mil (67.5mic)	0.6mil (15.2mic)	Acid-Free	10	Yes
LAT409-170	1 Side Laminate 1 Side Repositionable Adhesive	170' (91.4m)	25.3" (64.3cm)	2.7mil (67.5mic)	0.6mil (15.2mic)	Acid-Free	3	Yes

## XM4400

Offering three solutions in one easy-to-use package, the XM4400 makes professional document, signage and poster finishing up to 42" wide fast and easy.

Instantly applies laminate, adhesive or both without heat. Simply feed the item, push the button and trim. No smell, no mess, no waiting.

- Aggressive adhesive, coupled with high pressure rollers, improves both transfer and bonding qualities
- Patented supplies allow quick and easy application changes
- Even, edge-to-edge adhesive application
- Environmentally safe



As easy as 1, 2, 3



1. Insert Item



2. Press Button



3. Trim

**HYATT'S**  
All Things Creative

[www.hyatts.com](http://www.hyatts.com)  
910 Main Street  
Buffalo, NY 14202

[art@hyatts.com](mailto:art@hyatts.com)  
PH: 1-800-234-9288 ext. 302  
FX: 1-716-884-3943

# XM4400



## Product Specifications

Footprint	50.5" x 11" x 14.5" (129cm x 48cm x 37cm)
Weight/Packed Weight	155lbs (70kg) / 200lbs (91kg)
Document Thickness (max.)	0.10" (2.5mm) Up to 3/16"
Finished Document Width (max.)	42" (109.2cm)
Power Source	Electric
Cutter	Removable, replaceable cutter

## Product Supply Description

- **Permanent High-Tack Adhesive:** Extremely aggressive adhesive instantly creates a permanent bond on most surfaces. Sets instantly and will not peel. Acid-Free.
- **Repositionable Adhesive:** Allows items to be repositioned over and over. Easy removal from glass, walls, paper, and most other surfaces. Acid-Free.
- **Standard Use Laminate:** A high gloss film suitable for use on a variety of substrates. Superior adhesion. Compatible with most media. Acid-Free.
- **Combination—Laminate/Adhesive:** One of the laminate products described on the top surface and one of the acid-free adhesives described on the bottom surface. Acid-Free.

Part Number	Product Description	Material Length	Material Width	Laminate & Adhesive Combination Thickness (per side)	Mounting Adhesive Thickness	Adhesive pH	Mounting Adhesive Strength (1:10; 10-high)	PAT Approved
<b>Adhesive Application Roll Set</b>								
<span style="color: red;">●</span> AT4301-300	Permanent High-Tack	300' (91.4m)	42" (106.6cm)	N/A	0.6mil (15.2mic)	Acid-Free	10	Yes
<span style="color: green;">●</span> AT4306-170	Repositionable	170' (51.8m)	42" (106.6cm)	N/A	1.1mil (27.9mic)	Acid-Free	3	Yes
<b>Laminate Cartridges</b>								
<span style="color: blue;">●</span> DL3800-300	2-Sided Standard Use Laminate	300' (91.4m)	38" (96.5cm)	2.7mil (67.5mic)	N/A	Acid-Free	N/A	Yes
<span style="color: blue;">●</span> DL4300-300	2-Sided Standard Use Laminate	300' (91.4m)	42" (106.6cm)	2.7mil (67.5mic)	N/A	Acid-Free	N/A	Yes
<b>Combination One Side Laminate / One Side Adhesive Application</b>								
<span style="color: red;">●</span> LAT3801-300	1 Side Standard Use Laminate 1 Side High-Tack Adhesive	300' (91.4m)	38" (96.5cm)	2.7mil (67.5mic)	0.6mil (15.2mic)	Acid-Free	10	Yes
<span style="color: red;">●</span> LAT4301-300	1 Side Standard Use Laminate 1 Side High-Tack Adhesive	300' (91.4m)	42" (106.6cm)	2.7mil (67.5mic)	0.6mil (15.2mic)	Acid-Free	10	Yes